

Sms4less HTTP-gateway

All scripts

- All URLs have to be “url encoded” (see http://en.wikipedia.org/wiki/Query_string)
- Variables can be passed via GET or POST.
- If the script returns errors, they are separated by line breaks.

Mandatory variables

- login: user e-mail address
- password: user password

Return values

- unauthorized: wrong or no login

getcredits.php5

Get the current amount of credits available for the user.

Return value on success

The number of available credits.

Example GET URL

http://www.sms4less.be/_http/getcredits.php5?login=u&password=p

ordercredits.php5

Order extra credits.

Mandatory variables

- credits: the amount of credits, minimum 500

Optional variables

- invoice: request an invoice, 0 or 1

Return value on success

The cost in EUR.

Example GET URL

http://www.sms4less.be/_http/ordercredits.php5?login=u&password=p&credits=500&invoice=1

sendmessage.php5

Send a single message.

Mandatory variables

- message: the message body, maximum 160 characters, longer will be trimmed
- recipient: a valid international cellphone number: a plus sign (%2B), followed by the countrycode and the subscriber number (at least 9 digits)

Optional variables

sender: text that will appear instead of your cellphone number

Possible errors

- ERROR_TEXT_MISSING
- ERROR_INVALID_GSM
- ERROR_RECIPIENT_MISSING
- ERROR_NUMERIC_SENDER

Return value on success

- OK: if the script terminated successfully

Example GET URL

http://www.sms4less.be/_http/sendmessage.php5?login=u&password=p&message=hi%20there&recipient=%2B32001000000